PRODUCT SHEET

ELLIPSE 6636

Named after the meridians of our body—the paths along which our energy flows—the collection also brings to mind the meridian (or mid-point) of life with an invitation to relax and listen to your body and mind.



MODEL	тми	TUB		
Rolled deck	BMELOUM0T-XX	BMELOUM0N-XX		
Flat deck	BMELOUN0T-XX	BMELOUN0N-XX		
THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system		\$		
Jets		38		
1 heated backrest		Included		
MiaPlus [®] Control		Included		
Geysair®		Included		
AromaCloud®* BAROMAC		\$		
Illuzio Chromatherapy BCHRO6		\$		
2 nd heated backrest (WTS-1 zone) BSHB		\$		
TUB Soaker		\$		
AromaCloud [®] * BAROMAC		\$		
Illuzio Chromatherapy BCHRO6		\$		
WarmTouchShell [®] BWTS		\$		
DOT control		Included with therapy		
2 nd WarmTouchShell [®] BWTS2		\$		
FEATURES				

	<u> </u>				
Installation	n type		Drop-in & Undermount**		
No. of batl	ners	* *	Imp. gallo	ns	40
US gallons		48			
STANDAR	RD COLOR				
White 01	Biscuit 02				Included

Flat deck

OPTIONS (UPCHARGE APPLICABLE)		
COLOR		
Gray 05	\$	
WASTE & OVERFLOW 16" x 35" BOVER16-XX		
Chrome 07	\$	
White 01, Biscuit 02	\$	
Brushed Nickel 09, Polished Nickel 10, Oil-rubbed Bronze 11	\$	
CONTROL (TMU only)		
MiaMulti® BMIAM2-XX	\$	
IF REQUIRED BY CONSTRUCTION CODE OR INSTALLED WITH ITD		
16" x 35" Cable driven Brass waste & overflow kit BOVERBR-XX	\$	
 Don't forget to indicate flat or rolled deck. * The AromaCloud® is built into the deck. ** The AromaCloud® is not available with Undermount instal 	lation.	

TOTAL PRICE


\$









INSTALLATION











LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center waste	11 1/2"
В	Outside edge to overflow	4 5/8"
с	Total length	66"
D	Total width	36″
E	Bathing well length	42 3/8"
F	Bathing well width	22 1/4"
G	Deck width at backrest end	4 3/8″
н	Flat surface width	4 1/4"
I.	Rolled deck width	4 3/4"
J	Height from bottom of tub to top deck	21″
к	Height from bottom of tub to top deck	22″
L	Height from bottom of tub to bottom of lip	19 1/2"
м	Height from bottom of lip to top deck	2 1/2"
N	Height from waste to center of overflow	16 5/8"
0	Maximum water level	14 7/8″
Р	Slope of backrest	25°

AromaCloud[®] position

Control position when factory-installed (Mia® or DOT)

Turbine position (TMU)

- Indicates heated backrest (TMU)
- (Indicates WarmTouchShell® position (TUB)

TECHNICAL SPECIFICATIONS					
Hot water	Should be 70% of water capacity of TUB or greater.	Cutting template	# 90000055		
supply required Should be 70% of water capacity of 100 of greater.		Approx. shipping weight	100 lbs		
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 hz , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option ,	Turbine power	550 W		
	a second line is needed 15 A. 120 V, 60 hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	Air heater	600 W		
Other	There is a height difference for the rolled deck (see drawing Detail A).	WARRANTY			
Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).		Controls-LED-Geysair*	5 years		
		Bath & turbine*	20 years		

* Some restrictions apply | www.bainultra.com/warranty



The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.