


**ELEVATION** 

SECTION "A-A"



63" Tiled Barrier-Free Shower w/ 3/4" Threshold

CENTER DRAIN

## PRODUCT SPECIFICATIONS:

- Product material Acrylix<sup>TM</sup> surface with fiberglass composite reinforcement.
- Special installation instructions for this unit must be followed carefully.
- Certified to meet CSA B45.5/IAPMO Z124 Standard.
- Product has a Class B fire rating as determined by ASTM E-84 test method.
- This unit can be reinforced to meet the accessibility requirements for Type B dwellings upon request.
- When properly accessorized and installed, product meets requirements of ADA (2010 Std), ICC/ANSI A117.1-2017, ABA or UFAS.
- Simulated tile walls with ribbon design.
- Reinforced & slip resistant floor.
- Integral 1" [25mm] nailing flange.
- Integral 1" [25mm] floor nailing flange.
- Shower Floor: W- 60" x D- 30-5/8"
- Compartment Opening: W-60" x H-75 3/4"
- A shower door is only recommended if using our 2"x2" Acrylic Threshold.
- All dimensions +/- 1/2"
- Clarion Bathware reserves the right to change design and/or dimensions.
- Dimensions are the same for RE, MP, and all other versions of this

## 8333BF34CD

## 63" Tiled Barrier-Free Shower w/ 3/4" Threshold & Center Drain

44 Amsler Ave. Shippenville, PA 16254

Phone: (814) 226-5374 Toll Free: (800) 576-9228 Fax: (814) 226-0730

www.clarionbathware.com

Signatures For Approval: Customer:	Date:	Dwg. #   8333BF34CD-CUT
Arch./Engr:		
Quote #: Job Name:		Dwg. By: NMH DATE: 8/6/2021

## \*\*\* IMPORTANT NOTICE \*\*\*