

552TSD, 552TS Elm™ Tub Spout Series


Operation & Maintenance Manual



Model Numbers		Specifications
☐ 552TSD	Elm Diverter Tub Spout	5 7/8" diverter tub spout (552TSD) and 5 7/8" non-diverter tub spout (552TS) made from metal materials plated in standard polished chrome finish.
☐ 552TS	Elm Non-diverter Tub Spout	
Modifications		Warranty
□ -SBZ	Seasoned bronze finish	Limited Lifetime - to the original end purchaser in consumer installations.
□ -STN	Satin nickel finish	5 Years - for commercial installations.
		Refer to www.symmons.com/warranty for complete warranty information.
Note: Append appropriate -suffix to model number.		
Dimensions	S	

552TSD






Measurements		
А	Ø 2 5/8", 67 mm	
В	5 7/8", 149 mm	
С	1/2" - 14 NPT	

Required for Installation		
Teflon Tape		







Note: Dimensions are subject to change without notice.




552TSD, 552TS

Elm[™] Tub Spout Series

Operation & Maintenance Manual

Installation


1) Install tub spout to stub out pipe. Turn clockwise to secure.



Diverter Control

Note: 552TSD only.

1) Diverter lever in down position for tub spout operation.



2) Diverter lever in up position for shower operation.



Care and Cleaning

1) Clean finished trim area with a soft cloth using mild soap and water or a non-abrasive cleaner and then quickly rinse with water.