

Location:

552HS


Elm™ Hand Shower Unit


Specification Submittal



per	Specifications
3 Mode Hand Shower Assembly	3 mode hand shower assembly includes double checks, wall connection, cradle for hand shower mounting, flexible metal hose and standard 2.5 gpm (9.5 L/min) flow restrictor.
	Compliance
	-ASME A112.18.1/CSA B125.1
ıs	UPC
1.5 gpm (5.7 L/min) flow restrictor	C
2.0 gpm (7.6 L/min) flow restrictor	Warranty
30" slide bar in place of wall cradle on hand shower units	Limited Lifetime - to the original end purchaser in consumer installations. 5 Years - for commercial installations.
Seasoned bronze finish	Refer to www.symmons.com/warranty for complete warranty information.
Satin nickel finish	
appropriate -suffix to model number.	
	3 Mode Hand Shower Assembly 1.5 gpm (5.7 L/min) flow restrictor 2.0 gpm (7.6 L/min) flow restrictor 30" slide bar in place of wall cradle on hand shower units Seasoned bronze finish Satin nickel finish

Dimensions





Measurements	
А	2 1/8", 54 mm
В	Ø 3 1/4", 83 mm
С	1/2" IPS

Note: Dimensions are subject to change without notice.