



Location:

SYMMONS® Temptrol®

the smart choice™ Commercial

C-96-500-B30-V-X,
C-96-500-B30-V-TRM & C96500B30TRMTC
Shower/Hand Shower System & Trim
Specification Submittal



Feature Highlights

- Temptrol Commercial Shower/Hand Shower System or Trim
- Requires Temptrol® Pressure Balancing Tub/Shower Valve (included with C-96-500-B30-V-X)
- Requires Symmons Dual Outlet Diverter Valve (included with C-96-500-B30-V-X)
- Integral service stops allow water shutoff at valve for service (included with C-96-500-B30-V-X)
- Adjustable stop screw to limit hand turn (included with C-96-500-B30-V-X)
- Metal lever handles
- Dual checks for backflow protection
- 30" slide bar for hand shower
- 60" flexible metal hose
- 1 mode showerhead
- 1 mode hand shower
- 2.5 gpm (9.5 L/min) flow restrictor
- Tub spout not included
- Components shall be metal and nonmetallic construction, plated in standard Polished Chrome finish
- Available with TA-10 flow control spindle and T-12A cap assembly for Temptrol valve bodies installed with Test Cap (order p/n C96500B30TRMTC)

Model Numbers

- ☐ **C-96-500-B30-V-X**
Shower/Hand Shower System with Temptrol Pressure Balancing Tub/Shower Valve and Symmons Dual Outlet Diverter Valve
- ☐ **C-96-500-B30-V-TRM**
Shower/Hand Shower Trim, Temptrol Pressure Balancing Tub/Shower Valve and Symmons Dual Outlet Diverter valve ordered separately
- ☐ **C96500B30TRMTC**
Shower/Hand Shower Trim with TA-10 flow control spindle and T-12A cap assembly, must order Temptrol valve with Test Cap

Compliance

- ASME A112.18.1/CSA B125.1



Warranty

Limited Lifetime - to the original end purchaser in consumer/residential installations.
5 Years - for industrial/commercial installations.
Refer to www.symmons.com/warranty for complete warranty information.
Go to www.symmons.com/register to register your Symmons product.

Options/Modifications

- ☐ **-1.5** **CG** 1.5 gpm (5.8 L/min) flow restrictor
- ☐ **-2.0** 2.0 gpm (7.6 L/min) flow restrictor
- ☐ **-L1** Less showerhead (head only)
- ☐ **-L2** Less hand shower (wand only)
- ☐ **-L3** Less showerhead & hand shower wand
- ☐ **-L4** Less head, arm and flange
- ☐ **-L5** Less hand shower system (less bar/ cradle, hose, wand and elbow)
- ☐ **-L7** Less handle
- ☐ **-NS** **CG** Non-shared diverter valve
- ☐ **-REB** Rebuild trim kit, includes TA-10 and TA-4
- ☐ **-VB** Elevated vacuum breaker
- ☐ **Delete Suffix X** Less integral service stops
- ☐ **-CHKS** Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve


KITVP

*Order separately for Vandal Proof Kit.

Note: Append appropriate -suffix to model number.

Dimensions

Male 1/2" IPS thread must protrude 3/8" (10 mm) from finished wall for proper installation of street ell and flange.



Notes:

- 1) Valve body and piping not included and shown as reference only.
- 2) Plaster shield (p/n T-176) for dry wall, plaster or other type walls 1/2" or greater.
- 3) All dimensions measured from nominal rough-in.
- 4) Dimensions subject to change without notice.